

SEMI-AUTOMATIC BALANCES

Two pans for addition of weights to reach equilibrium of capacity. Double dial. Oil oscillation shock-absorber, with exterior adjustment. All supports are on bearings of agate. Stainless steel pan dia. 38 cm. Supplied without weights. Dimensions: 380 x 500 x 650 (h) mm. Weight: kg 25.



TL 341

TL 341 **BALANCE 10 KG CAPACITY**
50 g dial, 1 g sensitivity

TL 371 **BALANCE 30 KG CAPACITY**
250 g dial, 5 g sensitivity

TL 341/P **WEIGHT SET: 10.8 KG**
Cast iron 1 x 5 - 2 x 2 - 1 x 1 kg
Brass 1 x 500 - 1 x 200 - 1 x 100 g

TL 371/P **WEIGHT SET: 30.8 KG**
Cast iron 2 x 10 - 1 x 5 - 2 x 2 - 1 x 1 kg
Brass 1 x 500 - 1 x 200 - 1 x 100 g



TL 341/P

Weights	Chromium plated brass class M1 *	Tolerance	Polished brass standard	Tolerance
g. 1	PC 000/001	mg. 1	PO 000/001	mg. 5
g. 2	PC 000/002	mg. 1.2	PO 000/002	mg. 5
g. 5	PC 000/005	mg. 1.5	PO 000/005	mg. 10
g. 10	PC 000/010	mg. 2	PO 000/010	mg. 20
g. 20	PC 000/020	mg. 2.5	PO 000/020	mg. 30
g. 50	PC 000/050	mg. 3	PO 000/050	mg. 50
g. 100	PC 000/100	mg. 5	PO 000/100	mg. 60
g. 200	PC 000/200	mg. 10	PO 000/200	mg. 100
g. 500	PC 000/500	mg. 25	PO 000/500	mg. 250
kg. 1	PC 001	mg. 50	PO 001	mg. 400
kg. 2	PC 002	mg. 100	PO 002	mg. 600
kg. 5	-	-	PO 005	mg. 1250
kg. 10	-	-	PO 010	mg. 2500

* Tecnotest certified



Weights	Cast iron class M1 *	Tolerance
kg. 5	PC 005	mg. 250
kg. 10	PC 010	mg. 500
kg. 20	PC 020	mg. 1000

* Tecnotest certified

